



FALL ARRESTORS

Heavy duty MAXIPROTECT Fall Arrest Retractable Lifelines are designed to reduce vertical impact force on the body caused by falling from height.

MAXIPROTECT® Fall Arrestors provide continuous protection against falls. The Fall Arrestor automatically extends and retracts to allow freedom of movement.

MAXIPROTECT® Fall Arrestors are manufactured in a ISO 9001:2008 factory and all products are CE approved. Maximum rated load of 150kg.



Triple pawl brake system

SPECIFICATIONS - FALL ARRESTORS EN360 APPROVED

Model Number	Туре	Dia Width of rope (mm)	Length (m)	Weight (kg)
FAMP10	Steel wire rope	4.8	10	6.5
FAMP15	Steel wire rope	4.8	15	8.0
FAMP20	Steel wire rope	4.8	20	10.8

- · High strength ABS (thermoplastic) casing
- 150kg capacity for operator and tools
- Triple pawl brake system with energy dissipating mechanism
- · Lightweight, compact and durable
- Conforms to EN 360:2002 (SANS 50360:2003)
- . Minimum static strength 15kN
- · Side cable exit for smooth operation and reduced cable wear



- Top anchor point with built-in swivel limits lifeline twisting
- Buffer spring at cable exit protects block and allows for smooth operation
- Lower self-locking snap hook and swivel with built-in impact indicator for connecting directly to the safety harness
- Available in 10M, 15M and 20M wire rope lengths
- · Supplied with pull down cord